



Substitute Specification and Abstract (Marked-Up Version)

DEEP-ROLLING APPARATUS OF A DEEP ROLLING MACHINE FOR CRANKSHAFTS

BACKGROUND OF THE INVENTION

The present invention relates to a deep rolling apparatus of a deep rolling machine for crankshafts where two arms across from each other support a deep rolling ~~roller~~ head or a supporting roller head, whereby the supporting roller head is provided with two supporting rollers with parallel axes and the deep rolling ~~roller~~ head with at least one deep-rolling-work roller whose axis of rotation is in the same plane as the axis of rotation of the crankshaft and forms an angle with it, with a driving device that produces the closing and opening motion of the deep rolling apparatus ~~device~~ as well as the deep rolling force.

A deep rolling apparatus of this type is known e.g. from DE 299 10 214.9 and DE 202 00 926.2. -In either case the patents deal with deep rolling apparatuses provided with devices to avoid a collision of the tools with the ~~lubricators~~ oil collars of the pin journals of the crankshaft ~~lobes~~. Normally, two deep-rolling-work rollers are installed in pairs and at a distance from each other in a deep rolling ~~roller~~ head and enter the radii or indentation annular fillets between the ~~lobes~~ pin journals and ~~arms~~ the webs of the crankshaft under the action of the deep rolling force while the crankshaft rotates around its axis of rotation. The axes of rotation of the two deep-rolling-work rollers lay in the same plane as the axis of rotation of the crankshaft or are slightly offset relative to the axis of rotation of the crankshaft. The deep-rolling-work rollers are inclined outward in relation to the deep rolling ~~roller~~ head and ~~also assume this~~ form a sharp angle with the axis of rotation of the crankshaft.

Inside the deep rolling head the two deep-rolling-work rollers bear on a guide-back up roller ~~head~~ that is mounted in the deep rolling ~~roller~~ head in such manner that it cannot take over any forces in the longitudinal direction of the crankshaft.

Supporting roller heads may develop forces in axial direction, e.g. when the axis of one of the two supporting rollers of a supporting roller head is not exactly parallel with the axis of rotation of the crankshaft. In addition alignment errors in the alignment of the deep rolling toolhead, ~~knocking-run out~~ of the crankshaft, conical bearing surfaces of the main or ~~lobe-bearing~~ crank pin journals may provoke forces in axial direction, i.e. in the direction of the axis of rotation of the crankshaft that are undesirable due to incompatibility with a clean neat work result and the intensity of which depends on the intensity of the deep rolling force and the ~~existing-given~~ conditions of friction.

SUMMARY OF THE INVENTION

This leads to the object of the present invention, ~~consisting in~~ to provideing a guiding system that is suitable to absorb forces emanating from the deep rolling apparatus or generated at the deep rolling apparatus in the axial direction and thus to improve the ~~machining-work~~ results of deep rolling on the crankshaft.

According to the invention this object is attained ~~in that by providing~~ an axial guide roller, that is centered relative to the deep rolling head of a scissor-type deep rolling apparatus, having an axis of rotation perpendicular to the axis of rotation of the crankshaft and ~~with having~~ a diameter that is slightly ~~shorter-smaller~~ than the ~~distance space~~ between two ~~lubricators-oil collars~~ of a main or ~~lobe-pin~~ bearing journal of the crankshaft, ~~is provided in the scissor-like construction of the deep rolling roller head.~~

~~For an~~ In one embodiment of the deep rolling apparatus of the less frequent compact design, whereby the two arms of the deep rolling apparatus are connected to each other via a yoke, an axial guide roller is installed on the yoke and is centered relative to the deep rolling roller head whose axis of rotation is perpendicular to the axis of rotation of the crankshaft and has a diameter that is slightly ~~shorter-smaller~~ than the ~~distance space~~ between two ~~lubricators-oil collars~~ of a main or ~~lobe-pin~~ bearing journal of the crankshaft.

Since prevailing space availability usually does not permit a perpendicular positioning of the axial guide roller relative to the axis of rotation of the crankshaft, it is provided in

another advantageous embodiment that the rotational axis of the axial guide roller forms a sharp angle with a plane containing the axis of rotation of the crankshaft and that it is at a distance from the common plane of the rotational axes of the to supporting rollers. In both embodiments an axial guide roller delimiting an axial movement of the deep rolling apparatus in the longitudinal direction of the axis of rotation of the crankshaft is permanently installed therefore on the deep rolling ~~roller-head~~ or on the yoke and introduces forces acting in the same direction into the ~~lubricator-oil collar~~ of the crankshaft. The ~~placement-positioning~~ of the axial guide roller at a sharp angle does not affect the free space within the deep rolling machine which may also be required for the axial displacement of the crankshaft. The ~~placement-positioning~~ instead ~~leaves room~~ provides free space at the top that is ~~of sufficient size to serve as an~~ for the access space ~~for of a~~ measuring scanner that measures the ~~eyelie-uniform~~ running of the crankshaft in a known ~~mann~~er before and after the deep rolling process.

Instead of a single axial guide roller, a pair of axial guide rollers is also provided, with axes of rotation parallel to each other and at a distance from each other. However the possibility is also provided for the axes of rotation of a pair of axial guide rollers to be offset ~~as when~~ seen at an angle, perpendicularly to the axis of rotation of the crankshaft. Instead of axial guide rollers however, sliding bodies can also be provided in a known manner. ~~Greatly Other~~ advantageous embodiments are ~~indicated-claimed~~ in the sub-dependent claims.

The invention is described in further detail through two examples of embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a section through a deep rolling machine with a partial view of a crankshaft conveying device, whereby a deep rolling apparatus assumes its ~~perpre~~pre-closing position relative to a presented crankshaft,

Fig. 2 shows a section through the deep rolling machine and a section through a main bearing journal of the crankshaft, whereby the deep rolling apparatus is in its closing position,

Fig. 3 shows a section along line IV-IV of Fig. 4,

Fig. 4 shows the axial guide roller on a deep rolling apparatus designed ~~with~~ by the scissor-~~like~~type construction,

Fig. 5 shows the cross-section through a deep rolling ~~roller~~ head,

Fig. 6 shows the force parallelogram of uniform axial forces,

Fig. 7 shows the force parallelogram of non-uniform axial forces and

Fig. 8 shows a second embodiment of a deep rolling apparatus.

DETAILED DESCRIPTION OF THE INVENTION

A deep rolling machine 1 is designed with a driving device (not shown) ~~serving to the reception of~~ to rotate a crankshaft 3 ~~presented by~~ received from a crankshaft conveying device 2.

The driving device produces the rotational movement of the crankshaft 3 around its axis of rotation 4 during the deep rolling of the main ~~axle-pin~~ axle-pin journals 6 and ~~lobe-axle-crank pin~~ axle-crank pin journals 5. The axis of rotation 4 is thus located in the axis of rotation of the driving device.

The present ~~embodiment~~ description is ~~made for~~ limited to the deep rolling of the ~~lobe axle-one crank pin~~ axle-crank pin journal 5 of the crankshaft 3, since this is sufficient ~~in order to~~ to explain the object of the invention. A deep rolling apparatus 8 of ~~the~~ the scissor-~~like~~type construction is provided with two scissor arms 9, 10, a scissor pivot point 11, a drive system 12, a deep rolling ~~roller~~ head 13 and a supporting roller head 14 ~~is in~~ associated with the ~~lobe-axle-crank pin~~ axle-crank pin axle journal 5. The drive system 12 is equipped with an adjusting cylinder 15 and a ~~free-power~~ drive device 16. The adjusting cylinder 15 generates the closing and opening movement of the deep rolling apparatus 8, the ~~free power~~ drive device 16 produces the deep rolling force. The deep rolling apparatus 8 is hinged ~~via~~ through a hinging point 17 to an ~~rectangular~~ rectangular lever 19 capable of swiveling around an axis 18. The ~~rectangular~~ rectangular lever 19 can be swiveled by means of a piston cylinder unit 20.

The deep rolling machine 1 is designed ~~so in such a manner~~ that when the deep rolling apparatus 8 closes, at first the two supporting rollers 21, 22 of the supporting roller head 14 which have parallel axes and ~~then thereafter~~ the two deep rolling work rollers 23, 24 of the deep rolling roller head 13 come to ~~bear upon~~ into contact with the lobe axle crank pin journal 5.

Hereby the supporting roller head 14 executes a swiveling motion 35 around the hinging point 17 and the deep rolling ~~roller~~ head 13 a swiveling motion 36 around the scissor pivot point 11.

During the swiveling motions 35 or 36 of the supporting roller head 14 and the deep rolling ~~roller~~ head 13 in the closing direction, a collision with one of the two ~~lubricators~~ oil collars 25, 26 of the ~~lobe axle crank pin~~ journal 5 is avoided because the deep rolling ~~roller~~ head 13 is provided with an axial guide roller 27 that is transversal and centered relative to the supporting rollers 21, 22 and has a diameter 28 greater than the width 29 of the deep rolling ~~roller~~ head 13 but slightly smaller than the ~~distance space~~ 29a between the ~~lubricators~~ oil collars 25, 26 of the ~~lobe axle crank pin~~ journal 5.

The axial guide roller 27 is cylindrical on the outside. In the closed position of the deep rolling apparatus 8 Fig. 2 a clearance of approximately 0.25 mm is individually provided for the two free spaces 30, 31 between the ~~lubricators~~ oil collars 25, 26 and the axial guide roller 27.

The rotational axes 32 and 33 of the two supporting rollers 21 and 22 are in one and the same plane 34 which is at a distance s from a plane 38 containing the axis of rotation 4 of the crankshaft 3. The axis of rotation 7 of the axial guide roller 27 forms an ~~acute~~ sharp angle 37 with the plane 38 containing the axis of rotation 4 of the crankshaft 3, which is at a distance s from the common plane 34 of the axes of rotation 32 and 33 of the two supporting rollers 21 and 22 and is parallel.

The deep rolling apparatus shown in Fig. 4 corresponds to the deep rolling apparatus as shown in Figs. 1 and 2.

In the section through a deep rolling ~~roller~~ head as shown in Fig. 5, the deep rolling force 39 is exerted on the crankshaft 3 by the housing 40 via the ~~guide-back up~~ roller 41 mounted rotatably therein and the ~~deep-rolling-work~~ rollers 23 and 24. A representative force parallelogram is shown in Fig. 6 where the deep rolling force 39 is broken down into the two equal components 39' and 39''.

If an axial interference force 42 is exerted upon the housing 40 of the deep rolling ~~roller~~ head 13, a force parallelogram such as in Fig. 7 is obtained. Therein the deep rolling force 39 is broken down into the two components 39''' and 39'''. The two components 39''' and 39''' are obviously of different magnitude. Applied back to the section of Fig. 5 this means that the left ~~deep-rolling-work~~ roller 24 exerts a greater force 39''' on the crankshaft 3 than the right ~~deep-rolling-work~~ roller 23 with the component 39'''. The result of the deep rolling operation is accordingly different.

In Fig. 8 another ~~possible~~ embodiment of a deep rolling apparatus is shown. Instead of scissor arms as those on which the embodiment of Figs. 1 to 4 is based, a deep rolling apparatus 49 in compact form is ~~used~~ shown here. Accordingly, the two arms 43 and 44 are connected to each other via a yoke 45. A lever system 46 with two articulations 47 and 48 as well as with a corresponding drive (not shown) ensures the ~~swiveling-entering~~ of the deep rolling apparatus 49 into its working position. While the deep rolling head 13 is connected in a known manner to arm 43, the ~~supporting~~ roller head 50 is moved by a drive 51 into an opening and closing position relative to the crankshaft 3. An axial guide roller 52 projects from the yoke 45 in the direction of the axis 4 of rotation of the crankshaft 3. The axial guide roller 52 is rotatably mounted in a base 53 on the yoke 45. The support of the axial guide roller 52 in the base 53 may either be rigid, as shown in Fig. 8, or ~~can also~~ may have its own drive (not shown) that is similarly ~~suited as in case of~~ to the drive 51 to bring the axial guide roller 52 into a closing and opening position.

Instead of individual axial guide rollers 27 or 52, sliding elements can be provided and these, without being themselves rotatable, can be introduced into the ~~intervals~~space 29a between the two ~~lubricators~~oil collars 25 and 26. Instead of individual rollers 27 or 52, pairs of rollers with diameters 28 considerably smaller than shown in Fig. 8, but with outer circumferences sufficient to bridge the ~~distance~~space 29a between the ~~lubricators~~oil collars 25 and 26 can be provided. Here too, the principle applies again that instead of two individual axial guide rollers 27 or 52, sliding elements (not shown) are provided as known from DM GM 202 00 926.2.

~~The advantage of p~~Providing one axial guide roller 27, 52 on the deep rolling ~~roller~~ head 13 or on the yoke 45 of a deep rolling apparatus 8, 49 has the advantage over the known installation of one axial guide roller on the supporting roller head 14, that the axial guidance of the deep rolling apparatus 8, 49 relative to the crankshaft 3 can be more direct, so that possibly lacking rigidity in the device arm 9, 43 which supports the deep rolling ~~roller~~ head 13 as well as in the pivot point 11 between the two device arms 9, 10, 43, 44 can no longer affect the deep rolling results.

List of Reference Numbers

- 1 Deep rolling machine
- 2 Crankshaft conveying device
- 3 Crankshaft
- 4 Rotational axis of the crankshaft
- 5 ~~Lobe~~Crank pin
- 6 ~~Main bearing journal~~pin
- 7 Axis of rotation of the axial guide roller
- 8 Deep rolling apparatus
- 9 Scissor arm
- 10 Scissor arm
- 11 Scissor pivot point
- 12 Driving device
- 13 Deep rolling ~~roller~~ head
- 14 ~~Supporting~~ roller head
- 15 Adjusting cylinder
- 16 Force device
- 17 Hinging point
- 18 Axis
- 19 ~~Recta~~Angular lever
- 20 Piston-cylinder unit
- 21 ~~Supporting~~ roller
- 22 ~~Supporting~~ roller
- 23 ~~Deep rolling~~ Work roller
- 24 ~~Deep rolling~~ Work roller
- 25 ~~Lubricator~~Oil collar
- 26 ~~Lubricator~~Oil collar
- 27 Axial guide roller
- 28 Diameter of the axial guide roller
- 29 Width of the ~~supporting~~ roller head

- 29a ~~Distance~~ Space between the ~~lubricator~~ soil collars
- 30 Free space
- 31 Free space
- 32 Axis of the supporting roller
- 33 Axis of the supporting roller
- 34 Plane through axes 32 and 33
- 35 Swivel motion, counterclockwise
- 36 Swivel motion, clockwise
- 37 Sharp angle
- 38 Plane
- 39 Deep rolling force
- 39' Component of the deep rolling force
- 39'' Component of the deep rolling force
- 39''' Component of the deep rolling force
- 39'''' Component of the deep rolling force
- 40 Housing
- 41 ~~Guide~~ Back up roller
- 42 Axial interference force
- 43 Arm
- 44 Arm
- s Distance
- 45 Yoke
- 46 Lever system
- 47 Articulation
- 48 Articulation
- 49 Deep rolling apparatus
- 50 Supporting roller head
- 51 Drive
- 52 Axial guide roller
- 53 Base

Abstract

The present invention relates to the deep rolling apparatus (8) of a deep rolling machine 1 for crankshafts (3) in which two arms (9, 10) across from each other support a deep rolling ~~roller~~-head (13) or a supporting roller head (14). The supporting roller head (14) has two supporting rollers (21, 22) with parallel axes and the deep rolling ~~roller~~-head (13) has two ~~deep rolling work~~ rollers (23, 24) entering the radii or ~~indentation~~-fillets of the main bearing or crank pin journals or ~~lobe bearing~~ journals of the crankshafts (3). In one embodiment of the deep rolling apparatus (8) in scissor-like construction an axial guide roller (27) is provided on the deep rolling ~~roller~~-head (13) and is centered relative to the deep rolling ~~roller~~-head (13), its axis of rotation being perpendicular to the axis of rotation of the crankshaft (3). ~~and having~~ The axial guide roller (27) has a diameter that is slightly less smaller than the distance between two lubricators-oil collars (25, 26) of a main bearing journal or lobecrank pin journal (5) bearing of the crankshaft.